

THE OPEN-CIRCUIT SELF-CONTAINED BREATHING APPARATUS.

The Aeris Confort Type 2 is an open-circuit SCBA. It is fully compliant with the requirements of the most recent EN 137 standard, type 2 classification, and is suitable for a range of applications.

It has a high/medium pressure (HP/MP) compensated reducing valve, a harness with aramid-fibre straps, a full face mask, a positive pressure demand valve and an audible alarm built into the handle of the pressure gauge.

THE RANGE

Aeris Confort Type 2 - black harness - with Zenith demand valve and Panoramisque full face mask with five-point head harness without air cylinder (1825111)

Aeris Confort Type 2 - black harness - with Sx-Pro demand valve and Panoramisque full face mask with five-point head harness without air cylinder (1825216)



STANDARD FEATURES:

- Non-metallic, ergonomic, flexible backplate
- Three carry handles and an attachment point for a lifeline
- Comfort cushions on the shoulders and an aramid-fibre waist belt
- Excellent weight distribution of the apparatus on the hips
- Large adjustable fast-tightening shoulder strap buckles
- Washable harness
- Harness and straps in self-extinguishing aramid fibre in accordance with the requirements of the latest EN 137 Type 2 standard
- End-of-operation alarm whistle integrated into the pressure gauge with an antistatic HP/MP flexible hose
- HP/MP reducing valve with safety valve



GOOD TO KNOW

PANORAMASQUE FULL FACE MASK: its ergonomic design ensures it suits all face shapes and its wide-angle lens with anti-scratch coating ensures a panoramic field of vision without optical distortion (optional Triplex lens). The facepiece, internal half mask and skirt are made of high-performance EPDM (special polymer). Its structure provides optimum resistance in fire and chemical environments.

COMPATIBLE WITH BOTH QUICK-CLICK POSITIVE PRESSURE DEMAND VALVES:

- **Zenith automatic valve:** the valve is triggered automatically when connected to the mask and closed when disconnected. It guarantees impressive breathing performance regardless of the effort made by the user. It is equipped with two attachment points.
- **Sx-Pro first-breath-activated quick-click valve:** compact, ergonomic and robust, it offers excellent respiratory comfort regardless of the effort made by the user, thanks to minimal breathing resistance.

Equipped with two large attachment points so it can be donned or doffed easily while wearing gloves.

TECHNICAL DATA

Weight (backplate & harness & Zenith demand valve): 3,5 kg

High-pressure pneumatic gauge:

0-400 bar, photo-luminescent gauge, rubber protection and integrated alarm whistle

Alarm activation: 55 ±5 bar

Alarm volume: > 90 dBA

Approved temperatures: -30 à +60°C

Approvals: EN 137: 2006 Type 2, SOLAS, MED, IMO, MSC, ISO 23261-3



PANORAMASQUE FULL FACE MASK

Weight: 585 g

Full and Half Mask: EPDM

Eyepiece: PC

High-pressure regulator outlet: 7.5 bars

Approvals: EN136 - Classe III

ACCESSORIES



Compressed air cylinders

A range of cylinders (six to nine litres) that can be used for all types of application requiring self-contained breathing apparatus.

Steel or composite cylinders available