

## THE COMPLETE SCBA KIT FOR SELF-CONTAINED RESPIRATORY PROTECTION ON THE GO.

This next-generation self-contained breathing apparatus, which requires only minimal maintenance, is the perfect companion for all your tasks where there is a risk of oxygen deficiency or the presence of toxic gases. This all-in-one kit is delivered in a robust transport and storage case, making it a long-term investment. The R-PAS kit includes:

- a PAS Lite open-circuit self-contained breathing apparatus (OC-SCBA) and demand valve
- a Panorama Nova mask (without steel speech diaphragm)
- a mask bag
- a 6l 300bar cylinder made of lightened steel
- a transport case

This always-ready apparatus requires minimal maintenance. Next-generation pneumatic system:

- reducing valve pre-set in the factory: requires only minimal maintenance (standard replacement every ten years)
- high safety level: compliant with standard EN 137- (firefighting equipment)
- easy and comfortable to use

## TECHNICAL DATA



▶ <b>Weight incl. LDV</b>	2.7 kg
▶ <b>Size</b>	590 x 290 x 160 mm
▶ <b>Input Pressure</b>	0 - 300 bar
▶ <b>Nominal 1st stage output pressure</b>	7.5 bar
▶ <b>1st stage output flow</b>	> 1,000 l/min
▶ <b>LDV output flow</b>	> 400 l/min
▶ <b>Whistle activation pressure</b>	50 - 60 bar
▶ <b>Whistle Sound Level</b>	>90 dBA

▶ <b>Approvals</b>	EN 137 2006 Type 2 EN 14593 pt1 (when PAS ASV fitted) MED SOLAS II-2 Suitable for use in explosive atmospheres
--------------------	---



▶ <b>Weight</b>	550g
▶ <b>Mask body</b>	EPDM
▶ <b>Eyepiece</b>	PC
▶ <b>Clamping frame</b>	Red plastic housing
▶ <b>Approval</b>	EN 136



▶ <b>Size</b>	Height 510 mm, ø 139.5mm
▶ <b>Weight</b>	9.10 kg (full), 7.10 kg (empty)
▶ <b>Water Capacity</b>	6 liters
▶ <b>Free Air Capacity</b>	1636 liters
▶ <b>Working Duration</b>	41 min
▶ <b>Nominal Duration</b>	31 min
▶ <b>Service Pressure</b>	300 bars
▶ <b>Thread</b>	M18 x 1.5
▶ <b>Approval</b>	EN 12245:2009