



WEBBING MOBILE LIFELINE KIT

The webbing mobile lifeline is a temporary lifeline that is easy to transport thanks to its storage bag, which is connected to the lifeline. The lifeline can be used by 2 people simultaneously and can be adjusted from 5m to 20m.

Attachment via permanent or temporary anchor slings or straps.

Delivered in a storage bag.

FEATURES:

Breaking Strength: >20 KN

Maximum SAG: 2m

Approval: EN 795 Class B

Weight: 4.54 Kg

Operating Temperature: -30°C to +50°C

Strap :

Width 35 mm , in polyester
 Resistance: > 4500 daN

Ratchet tensioner :

Dichromate steel
 Resistance: > 1500 daN



Line deflection in the case of a fall			
Length of the line	Number of users	SAG	Pull on the end
5 meters	2	0.9 m	1450 daN (3,260 lbf)
10 meters	2	1.7 m	1300 daN (2,922 lbf)
20 meters	2	3.5 m	1200 daN (2,698 lbf)

TITAN WEBBING ANCHORAGE SLING

The anchorage sling provides a secure anchor point for a fall protection device, for small-scale projects. With its high breaking strength, it provides a secure anchor point for a fall arrest device, and is easy to install.

FEATURES:

Description: Orange strap with black stripes

Material: Polyamide Ø20mm

Approval: EN 795b : 1996 / EN 566

Breaking Strength:

> 10 KN for EN 795b :1996

> 22 KN for EN 566

Length and Weight :

0.6m = 80g

0.8m = 105g

1m = na

1.2m = 160g

1.5m = 185g

