

THE MULTI-GAS DETECTOR WITH AN INTEGRATED PUMP, SUITABLE FOR CONFINED SPACES.

The GasAlertMax XT II detector is a simple, smart and affordable way to make sure your site is compliant.

Users feel safe and the number of incidents is reduced. Everyone will be able to do more, and that means savings realised from business continuity and productivity.

With its one-button operation and motorised pump, the GasAlertMax XT II detector can monitor up to four gases. It's the perfect solution for intelligent remote sampling in confined spaces.

The GasAlertMax XT II is fully compatible with MicroDock II, the automated test and calibration system.



TECHNICAL DATA

Size: 5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm

Weight: 11.5 oz. / 328 g

Temperature: -4 to 122°F / -20 to 50°C

Humidity: 10 - 100% RH (non-condensing)

Protection Class: IP66/67


Alarms: Visual, vibrating, audible (95 dB) - Low, High, TWA, STEL, OL (over limit), Low Battery, Pump

Tests: Audible/visual alarms on activation, sensors, battery, pump and circuitry (continuous)

Operating time: 13 hours (32°F / 0°C), 8 hours (-4°F / -20°C)
Recharges in 6 hours

Approvals: ATEX II 1 G Ga Ex ia IIC T, IECEx a Ex ia IIC T, CE

Warranty: 3 years standard - MED 2 years



SENSOR SPECIFICATIONS

Gas	Measuring Range	Resolution
H ₂ S	0-200 ppm	1 / 0.1 ppm
CO	0-1,000 ppm	1 ppm
O ₂	0-30.0% v/v	0.1% v/v
Combustible	0-100% LEL	1%LEL
Combustible	0-5.0% v/v	0.1% v/v

Sensor alarm setpoints can be adjusted by the user. These setpoints are automatically displayed during instrument start up.



SPECIFICATIONS:

- Integrated sampling pump with dependable diaphragm technology
- Best-in-class block detection with its semi-conductor pressure sensor
- Multi-language interface: five languages
- Simple detector management with Fleet Manager II and Safety Suite
- Data and event logging