

THE SMALLEST, LIGHTEST, MOST AFFORDABLE MULTI-GAS DETECTOR ON THE MARKET.

The small and compact GasAlertMicroClip provides affordable protection from atmospheric gas hazards.


The IntelliFlash system provides continuous visual assurance that the multi-gas detector is compliant and operating correctly.

With its one-button operation, it is incredibly easy to use and significantly reduces user training time.

Two versions are available:

GasAlertMicroClip XL, which has an oxygen sensor with a two-year service lifetime and a two-year warranty.

GasAlertMicroClip X3, which has an all-new oxygen sensor that operates continuously for five years (with no replacement costs during the detector's service lifetime) and a three-year warranty.



TECHNICAL DATA

Size: 4.4 x 2.4 x 1.2 in. / 11.3 x 6.0 x 3.2 cm

Weight: 6.7 oz / 190 g (XL) - 6.3 oz / 179 g (X3)

Battery type: Lithium-polymer rechargeable battery pack

Operating time: 18 hours, recharge in less 6 hours

Temperature: -4 to +122°F / -20 to +50°C

Humidity: 5-95% RH (non-condensing)

Protection Class: IP68

Alarms: Visual, vibrating, audible (95 dB) - Low, High, TWA, STEL, OL (over-limit)

Test: Audible/visual alarms on activation; sensors, battery and circuitry (continuous)

Approvals: ATEX : II 1 G Ex ia IIC T4, IECEx: Ex ia IIC T4 G, EC

Warranty: including all sensors*
Two-year (Honeywell BW™ MicroClip XL)
Three-year (Honeywell BW™ MicroClip X3)
**Note: Battery is guaranteed to have 12 hour runtime during warranty period under normal operating temperature of 4°F / -20°C to 122°F / 50°C*

SENSOR SPECIFICATIONS

Gas	Measuring Range	Resolution
H ₂ S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O ₂	0-30% v/v	0.1% v/v
Flammable	0-100% LEL	1%
Flammable	0-5.0% v/v	0.1%

The alarm thresholds are adjustable by the user before and after the detector's activation with the IntelliDoX station.

SPECIFICATIONS

- Compact, lightweight design with one-button operation
- Designed for a wide range of harsh environments and extreme temperatures
- Automated battery, sensor and electronics self-test
- Wide-angle flash, together with audible and vibrating alerts
- Internal data logging and event logging capacity so information can be downloaded at a later date
- Compatible with the MicroDock II and IntelliDoX stations as well as the Fleet Manager and Safety Suite software

THE BE ATEX SOLUTION

GASALERTMICROCLIP XL PACK:



- A Two-year service package includes:
- GasAlertMicroClip XL detector (can be configured to detect up to four gases)
 - Two-year service in our workshop: three calibrations + three filter changes + return shipping costs

GASALERTMICROCLIP X3 PACK:

- A Three-year service package includes:
- GasAlertMicroClip X3 detector (can be configured to detect up to four gases)
 - Three-year service in our workshop: five calibrations + five filter changes + return shipping costs

Lots of sampling, comfort and safety accessories are compatible with the solutions in the BW By Honeywell range.



LEATHER CARRYING HOLSTER (MC2-LC1)

Protect your detector from dust and dirt with this leather carrying holster.



AUXILIARY FILTER KIT (MC-AF-K1)

Easily attaches in the field to protect the internal filter. Supplied with 1 filter adaptor and 5 auxiliary filters.



VEHICLE POWER ADAPTOR (GA-VPA-1)

This power adaptor plugs into the cigarette lighter, so you can easily charge your detector while you're on the move.



INFRARED CONNECTIVITY KIT (GA-USBT-IR)

Download your data and access the detector's configuration options from a computer.



FIVE-UNIT CRADLE CHARGER (MC2-C01-MC5)

Charge five detectors or batteries simultaneously. Just slip them into the charger and wait until the battery icon on the screen indicates that it has finished charging.



CONFINED SPACE KIT GASALERTMICROCLIP (MC-CK-DL)

Includes: a leather carrying case, an infrared connectivity kit, a 0.5-LPM regulator, a 3m sampling hose with a quick-connect fitting, a sampling probe and a hard carrying case with pockets in the lid and a foam interior.

BW CONNECT



With the BW Connect, you can transform your standard detector into a wireless gas monitoring device. This adaptor can be attached to the detector and paired with any smartphone via Bluetooth®.

Together with the Honeywell TouchConnect™ app, it provides real-time visibility of staff safety:

- Concentration readings from the gas detector
- Location of the worker
- Gas alarms
- Device compliance (gas test and calibration)

TECHNICAL DATA

Size: 1.53 x 1.37 x 0.41 in. / 39 x 35 x 10.6 mm

Weight: 0.75 oz / 21.5 g

Temperature: -20°C to +55°C / -4°F to +131°F

Humidity: 5-95% RH (non-condensing)

Display: Red and Green LEDs

Technology: Bluetooth® Low Energy (BLE)

Wireless range: Up to 10 m/ 33' (with line of sight)

Operating time: Up to 12 months, non-rechargeable

Protection Class: IP66/68C

Approvals: ATEX II 1G Ex ia IIC T4 Ga, IECEx SIR 18.0031, EC

Warranty: 1 year

